

UNCLASSIFIED

AD NUMBER

AD803078

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; FEB 1953. Other requests shall be referred to Ballistic Research Laboratories, Aberdeen Proving Ground, MD 21005.

AUTHORITY

BRL D/A ltr, 22 Apr 1981

THIS PAGE IS UNCLASSIFIED

REFERENCE COPY

BRL

TECHNICAL NOTE No. 772

FEBRUARY 1953

Dimensionless Treatment of Vacuum Trajectory

L. G. KOLLENDER

A. S. GALBRAITH


The Ballistic Research Laboratories Technical Note is designed for use within the laboratories or for issuing available information, when the occasion demands speed.

The contents of this paper are of the nature of advance information and may be extended or otherwise revised.

BALLISTIC RESEARCH LABORATORIES



ABERDEEN PROVING GROUND, MARYLAND



BALLISTIC RESEARCH LABORATORIES

TECHNICAL NOTE NO. 772

February 1953

DIMENSIONLESS TREATMENT OF VACUUM TRAJECTORY

L. G. Kollender

A. S. Galbraith

Project No. TB3-0108K of the Research and
Development Division, Ordnance Corps

ABERDEEN PROVING GROUND, MARYLAND

This page was intentionally left blank

BALLISTIC RESEARCH LABORATORIES

TECHNICAL NOTE NO. 772

LGKollenderASGalbraith/plg
Aberdeen Proving Ground, Md.
February 1953

DIMENSIONLESS TREATMENT OF VACUUM TRAJECTORY

ABSTRACT

By the use of dimensionless variables the initial velocity is eliminated and the initial elevation is the only parameter distinguishing one trajectory from another. All vacuum trajectories have the same maximum ordinate and time of flight.

This page was intentionally left blank

The vacuum trajectory as a basis of investigation can only give limiting values and indicate the parabolic shape of the trajectory and the approximate time relations. The only force acting is that of gravity which is assumed to produce an acceleration of constant magnitude g . For heavy projectiles the vacuum trajectory is sufficiently accurate for many purposes.

It has been found in the course of computing trajectories that for a reasonable approximation it is more convenient to use dimensionless variables and reduce the amount of work usually involved. All trajectories with the same initial elevation are identical if the aforementioned variables are used.

Definitions:

Let t be the time after firing, x the horizontal distance and y the vertical distance, positive upwards from the muzzle; θ the angle of the trajectory with the horizontal and θ_0 the initial angle of elevation; v the magnitude of velocity and v_0 the initial or muzzle velocity; g the acceleration due to gravity; and let $\dot{x} = \frac{dx}{dt}$, $\dot{y} = \frac{dy}{dt}$

$$\text{Then: } \ddot{x} = 0$$

$$\dot{x} = \dot{x}_0 = v_0 \cos \theta_0$$

$$x = \dot{x}_0 t$$

$$\text{and } \ddot{y} = -g$$

$$\dot{y} = \dot{y}_0 - gt = v_0 \sin \theta_0 - gt$$

$$y = -\frac{1}{2}gt^2 + \dot{y}_0 t$$

$$v^2 = \dot{x}^2 + \dot{y}^2 = \dot{x}_0^2 + \dot{y}_0^2 - 2\dot{y}_0 gt + g^2 t^2$$

$$\frac{\dot{v}}{v} = \frac{-g\dot{y}}{v^2}$$

$$\text{Arc length } s = \int \sqrt{v_0^2 - 2\dot{y}_0 gt + g^2 t^2} dt = \frac{1}{2g} \left[\dot{y}_0 v_0 - \dot{y} v + \dot{x}_0^2 \log \left(\frac{v - \dot{y}}{v_0 - \dot{y}_0} \right) \right]$$

where the subscript zero denotes the value when $t = 0$

$$\frac{dv/ds}{v} = \frac{g\dot{y}}{v^3}$$

Definitions: In dimensionless variables

$$\text{Let } c = \frac{v_o \sin \theta_o}{g} = \sqrt{\frac{2y_{\max}}{g}} = \frac{\dot{y}_o}{g},$$

$$T = t/c, \quad X = x/gc^2, \quad Y = y/gc^2$$

$$\text{Then: } \frac{d^2 X}{dT^2} = 0$$

$$\frac{dX}{dT} = \frac{dx}{dt} \cdot \frac{dt}{dT} = \frac{\dot{x}}{gc^2} \cdot c = \cot \theta_o$$

$$X = T \cot \theta_o$$

$$\text{and } \frac{d^2 Y}{dT^2} = -1$$

$$\frac{dY}{dT} = \frac{\dot{y}}{gc^2} \cdot c = 1 - T$$

$$Y = T - 1/2 T^2$$

$$\text{Let } V^2 = \left(\frac{dX}{dT} \right)^2 + \left(\frac{dY}{dT} \right)^2 = \cot^2 \theta_o + (1-T)^2$$

$$\text{and } S = \int_0^T \sqrt{\cot^2 \theta_o + (1-T)^2} = \int_0^T V dt$$

$$\text{Then } S = \frac{s}{gc^2} = 1/2 \left[V_o \frac{dY}{dT} \Big|_o - V \frac{dY}{dT} + \left(\frac{dX}{dT} \Big|_o \right)^2 \log \frac{V - \frac{dY}{dT}}{V_o - \left(\frac{dY}{dT} \right)_o} \right]$$

$$\text{Now } \frac{dV}{dS} = \frac{dV}{dT} \cdot \frac{1}{V} \quad \text{and} \quad V \frac{dV}{dT} = -(1-T)$$

$$\text{so } \frac{\frac{dV}{dS}}{V} = \frac{T-1}{V^3} = \frac{T-1}{\left[\cot^2 \theta_o + (1-T)^2 \right]^{\frac{3}{2}}}$$

For any vacuum trajectory the maximum ordinate is $\frac{1}{2}$ and occurs at $T = 1$, impact occurs at $T = 2$; and the range is $2 \cot \theta_0$. Then by simple substitution one can get results in the usual independent variables.

The rate of change of the trajectory angle θ is given by $\frac{d\theta}{dS} = \frac{\cot \theta}{V^3}$

$$\text{For } v^2 = (gc^2)^2 \left[\left(\frac{dX}{dT} \right)^2 + \left(\frac{dY}{dT} \right)^2 \right] \frac{1}{c^2} = g^2 c^2 V^2$$

$$\frac{d\theta}{dS} = \frac{d\theta}{ds} \cdot gc^2 = \frac{-g \cos \theta}{g^2 c^2 V^2} \cdot gc^2 = \frac{-\cos \theta}{V^2}$$

$$\cos \theta = \frac{\dot{x}}{V} = \frac{gc^2 \frac{dX}{dT} \cdot \frac{1}{c}}{gcV} = \frac{\cot \theta_0}{V}$$

$$\therefore \frac{d\theta}{dS} = \frac{-\cot \theta_0}{V^3}$$

The points of inflection of $\frac{d\theta}{dS}$ vs S are at $T = 1 \pm \frac{\cot \theta_0}{V^3}$

In figure 1 are shown three graphs of V versus S/S_w and three graphs $\frac{dV}{dS}$ versus S/S_w . The arc length S has been normalized by dividing by the total length of the trajectory, S_w .

L. G. Kollender

L. G. KOLLENDER

A. S. Galbraith

A. S. GALBRAITH

GLOSSARY OF SYMBOLS USED

The subscript zero on a symbol means that it is to be evaluated at the point where the initial conditions are applied.

The dot over a symbol means differentiation with respect to time.

A.

g = acceleration due to gravity

s = arc length along trajectory from muzzle

t = time after firing

θ = angle of trajectory above horizontal

v = magnitude of velocity

x = horizontal distance or range

y = vertical distance or altitude

B.

$c = (v_0 \sin \theta_0)/g$

$S = s/gc^2$ = dimensionless arc length

$S_w = S$ at impact


$T = t/c$

θ_0 = angle of departure

$V = v/gc^2$ = dimensionless velocity

$X = x/gc^2$ = dimensionless horizontal co-ordinate

$Y = \frac{y}{gc^2}$ = dimensionless altitude



DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>
2	Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTB - Bal Sec
2	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: Re3
2	Commander Naval Ordnance Test Station Inyokern P. O. China Lake, California Attn: Technical Library & Editorial Section
2	Commander Naval Proving Ground Dahlgren, Virginia
2	Commanding General Redstone Arsenal Huntsville, Alabama